



Ground Cover Industries, Inc.

SPECIFICATION DATA

395 Series – PERFORMANCE CHOICE LANDSCAPE FABRIC

395 Series Performance Choice landscape fabric is a pointbonded polypropylene fabric used in landscape applications. The fabric allows air, water, and nutrients to pass through. This fabric should be covered with mulch, rock, or similar to prevent degradation from exposure to sunlight.

Property	Test Method	Unit	Minimum Average
Weight	ASTM D 5261	OZ/SY	3
Grab Tensile	ASTM D 4632	LBS	MD 46 XMD 74
Grab Elongation	ASTM D 4632	%	MD 116 XMD 77
Trapezoid Tear Strength	ASTM D 4533	LBS	MD 17 XMD 34
CBR Puncture Resistance	ASTM D 6241	LBS	95
Water Flow	ASTM D 4491	GPM/FT ²	51
Thickness	ASTM D 5199	MILS	18

PROPERTY

Roll Sizes

TYPICAL

3'x50', 3'x100'

4'x50', 4'x100'

3',4',6',8',12'x300'

Disclaimer: Ground Cover Industries, Inc. assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. Ground Cover Industries, Inc. disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specifics. The end user assumes sole responsibility for the use of this information and product.

The property values listed above are subject to change without notice. © 2015 Ground Cover Industries, Inc.

GROUND COVER INDUSTRIES, INC.
PO Box 1933 - Santa Rosa Beach, FL 32459
817-633-4020 / 817-633-4023 fax

