



Ground Cover Industries, Inc.

SPECIFICATION DATA

395 Series - PERFORMANCE CHOICE LANDSCAPE FABRIC

395 Series - PERFORMANCE CHOICE LANDSCAPE FABRIC is made of 100% polypropylene fibers with ultra violet stabilizers and creates a micro heating environment for seed germination and seedling growth. Frosty Choice will substantially increase your seed germination rate compared to using straw. Polypropylene is stable within a pH range of 2 to 13.

PROPERTY	TEST METHOD	TYPICAL
Fabric Color		Black
Weight	ASTM D-3776	3 oz/sy
MD Tensile Strength(lbs)	ASTM D-5034	55
MD Elongation %	ASTM D-5034	40
CD Tensile Strength	ASTM D-1682-64	50
CD Elongation %	ASTM D-1682-64	80
Thickness (mls)	ASTM D-1777	24.4
Permittivity(hydrophilic only*)	ASTM D-4491	.5
Water Flow(gallons/sf/min)	ASTM D-4491	40

*Maximum Average Roll Value

PROPERTY	TYPICAL
Roll Sizes	3' x 300' 4' x 300' 6' x 300' 8' x 300' 12' x 300'

*Hydrophilic treated fabric allows air/water to pass through easier.

It suppresses weed growth by minimizing light penetration.

Fabric is treated to minimize UV light exposure degradation. (Always cover with stone or mulch)

Disclaimer: Ground Cover Industries, Inc. assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. Ground Cover Industries, Inc. disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specifics. The end user assumes sole responsibility for the use of this information and product.

The property values listed above are subject to change without notice. 2015 Ground Cover Industries, Inc.

GROUND COVER INDUSTRIES, INC.
PO Box 1933 - Santa Rosa Beach, FL 32459
817-633-4020 / 817-633-4023 fax

